



Lila-LAB GmbH
Am Eichenhain 2 – D-31552 Rodenberg
Tel. 05723 / 74 96 14
info@lila-lab.de



Midea MD-86L358

LED-Display: -86°C Ultratiefkühlschrank mit VIP Isolation und LED-Display

- 4 Fächer
- 2 isolierte Innentüren mit Gummidichtlippe
- Abschließbare Tür mit massivem Metallgriff, vorbereitet für zusätzliches Vorhängeschloss
- Außengehäuse aus einbrennlackiertem Stahlblech
- Innengehäuse mit abgerundeten Ecken zur leichten Reinigung
- Gehäuseisolation des Midea MD-86L358 mit Vakuumpaneelen, eingeschäumt in Polyurethan
- Beheizte Türdichtung verhindert Eisbildung und erleichtert die Türöffnung
- Zwei serienmäßige Durchführungen je Ø 25 mm für Kabel und Schläuche bzw. externen Temperaturfühler
- Einstufige Kältemaschine für einen leisen und sparsamen Betrieb
- FCKW-freies Kältemittelmix mit einem GWP von 0
- Microprozessorsteuerung aller Einstellungen, Alarm- und Diagnosefunktionen
- LED-Display mit digitaler Anzeige der Innenraumtemperatur, batteriegepuffert für 48 Stunden bei Stromausfall
- USB-Schnittstelle zum Auslesen der Temperaturdaten der letzten 10 Jahre
- RS485-Schnittstelle zur Einbindung in ein bestehendes Netzwerk
- Alarmfunktionen für Über- Untertemperatur, Stromausfall, Türverschluss, Akkuschwäche, zu hoher Umgebungstemperatur, Übertemperatur am Kondensator
- Alarm erfolgt optisch, akustisch sowie als Fernalarm über einen potentialfreien Kontakt
- Gerät Midea MD-86L358 steht auf Rollen, (feststellbar)



Lila-LAB GmbH
Am Eichenhain 2 – D-31552 Rodenberg
Tel. 05723 / 74 96 14
info@lila-lab.de

Technisches Datenblatt
Midea Ultratiefkühlschrank
Model: MD-86L358

Application, Rating, & Electrical Data

Application	ULT freezer
Storage Volume (L/Cu.Ft)	358/12.64
Temperature Range	-40°C to -86°C
Default Set Point	-81°C
Power	220-240 ~V/50Hz 115-V/60Hz
Current	5.3A 8.5A
Power Cord Length	1.7m
Certification	CE
Door type	Solid door
Application Environment	Non-corrosive, non-flammable, non-explosive
Ambient Operating Temperature	10°C-32°C

Refrigeration

Refrigeration System	Self-cascade
Compressor	Hermetic
Condenser Type	Air cooling
Expansion Device	Capillary tube
Evaporator Type	Built-in
Defrost Method	Manual defrosting
Refrigerant	Mix refrigerant

Controller / Configuration Settings

Display screen	LED
Controller Type	Microprocessor
Security	Lockable door, password protected settings
Control Sensor	PT1000, stainless steel
Communication Ports	USB, Remote alarm contacts
Power Failure Alarm	Yes
High/Low Alarms	Yes, fully adjustable
Door Ajar Alarm	Yes
Download	Yes, via USB, PDF
Temperature Log	Yes, download via USB
Battery Back-up	Yes, 52 hr display and alarm back-up Rechargeable 12V, lead acid

Performance Characteristics (normal operating conditions)

Uniformity (°C)	±5.0
Recovery to -75°C after 1 min door opening (min)	27.5
Temperature fluctuation (°C)	<5.7
Energy consumption (kWh/day)	9.7
Noise emission (dB)	50
Heat rejection (BTU/hr)	3521
Pull-down time to -81°C (min)	216

Typical Temperature Map

	test 1	test 2	test 3	test 4	test 5	test 6	test 7	test 8	test 9
Avg	-81.09	-81.35	-82.76	-82.28	-82.77	-82.42	-81.39	-81.98	-82.24
Max	-78.90	-78.70	-80.80	-80.00	-80.60	-80.30	-80.00	-80.80	-81.00
Min	-82.50	-83.50	-84.60	-84.20	-84.50	-84.20	-82.80	-83.20	-83.50

Midea Biomedical, Trademarks are the property of their respective owners. Drawings are not for engineering use, and specifications may change. Not all products are available in all countries, so please check with your local sales representative for details.




Dimensions and Construction


Interior (w x h x d)mm	450*583*1326 mm
Exterior (w x h x d)	795*885*1855 mm
Access Port	2 Access Port- for external monitoring probe(s) (25 mm diameter)
shelf	3 49 kg max capacity
Wheels	4/Omni-directional 2/leveling feet
Net Weight	160 kg
Gross Weight	206 kg

All performance data from 358L ULT freezer, 25 ambient, -81°C


Uniformity



Cooling Speed



DOR 1 minute



Temperature recover curve

