



Lila-LAB GmbH
Am Eichenhain 2 – D-31552 Rodenberg
Tel. 05723 / 74 96 14
info@lila-lab.de

Haier Biomedical
Intelligent Protection of Life Science

Haier HYC-509T

+5°C Premium Pharmazeutischer Kühlschrank Touch-Display



- Inklusive Glastür
- 509 Liter mit Geregelter Umluftkühlung
- Mikroprozessor gesteuertes
- 10“ Touch-Display
- Glastür
- LED-Innenlicht
- Umweltfreundliches Kältemittel (R600a) mit einem sehr geringen Energieverbrauch
- Anzeige der Temperatur und der Gerätezustände
- Abschließbar
- Optische und Akustische Alarmer für Temperaturabweichungen und andere Gerätezustände
- Sehr homogene Temperaturverteilung durch geregeltes Umluftkühlsystem ($\pm 2^{\circ}\text{C}$)
- Automatisches Abschalten bei öffnen der Fronttür
- Automatische Abtaufunktion mit Tauwasserverdunstung
- Sehr leise, lediglich 40 dB(A) für ein angenehmes Arbeiten
- Selbstschließende Tür
- Kabeldurchführung
- Potentialfreier Kontakt
- USB-Schnittstelle



Lila-LAB GmbH
Am Eichenhain 2 – D-31552 Rodenberg
Tel. 05723 / 74 96 14
info@lila-lab.de

Haier Biomedical
Intelligent Protection of Life Science

Technisches Datenblatt
Haier Biomedical Pharmazeutischer
Kühlschrank
Model: HYC-509T

Model		HYC-509T	
Technical Data	Cabinet Type	Upright, Single Glass Door	
	Climate Class	N	
	Cooling Type	Forced Air Cooling	
	Defrost Mode	Auto	
	Refrigerant	R600a	
	GWP (global warming potential)	20	
	Sound Level (dB(A))	40	
Performance	Temperature Range (°C)	2-8	
Control	Will the fan stop automatically when opening the door	Y	
	Controller	Microprocessor	
	Display	Touchscreen	
Electrical Data	Power Supply (V/Hz)	220-240/50/60	
	Electrical Current (A)	1.85	
Performance Characteristics	Temperature Sensor	PT100 + NTC	
	Power Consumption (kWh/24h)	5.9	
Dimensions	Capacity (L/Cu.Ft)	509/17.97	
	Net/Gross Weight (approx)	kg	180/215
		lbs	396/473
	Interior Dimensions (W*D*H)	mm	593*385*1500
		in	23.21*22.9*58.8
	Exterior Dimensions (W*D*H)	mm	693*813*1981
		in	27.1*31.9*77.7
	Packing Dimensions (W*D*H)	mm	835*915*2170
		in	32.9*36.0*85.4
	Container Load (20'/40'/40'H)	14/28/28	
Alarms	High/Low Temperature	Y	
	High Ambient Temperature	Y	
	Door Ajar	Y	
	Power Failure	Y	
	Low Battery	Y	
	Sensor Error	Y	
	Communication Failure	Y	
	Remote Alarm	Y	
	Audible and Visual Alarm	Y	
Accessories	Condensenser Overheat	Y	
	Caster	Y	
	Foot	Y	
	Porthole	Y	
	Test Hole	Y	
	Shelves/Drawers	6 on each side, clearance 19.5cm/Optional	
	Drawer Material	Steel Wire Dipping Plastic	
	USB Interface	Y	
Material	Exterior Material	Painted Steel	
	Interior Material	Painted Steel/Optional Stainless Steel	
	Door Thickness (mm)	50	
	Cabinet Thickness (mm)	50	
	Shelves Material	Steel Wire, Coated with Plastic	
	No. of Shelves	6	
Others	Certification	CE, UKCA, DIN13277 (Optional)	