



Lila-LAB GmbH
Am Eichenhain 2 – D-31552 Rodenberg
Tel. 05723 / 74 96 14
info@lila-lab.de

Haier Biomedical
Intelligent Protection of Life Science

Haier HYC-290

+5°C Pharmazeutischer Kühlschrank Inklusive Glastür



- 290 Liter mit Geregelter Umluftkühlung
- Mikroprozessor gesteuertes Digitaldisplay Glastür
- LED-Innenlicht
- Umweltfreundliches Kältemittel (R600a) mit einem sehr geringen Energieverbrauch
- Anzeige der Temperatur und der Gerätezustände
- Abschließbar Optische und Akustische Alarme für Temperaturabweichungen und andere Gerätezustände
- Sehr homogene Temperaturverteilung durch geregeltes Umluftkühlsystem ($\pm 2^{\circ}\text{C}$)
- Automatisches Abschalten bei öffnen der Fronttür
- Automatische Abtaufunktion mit Tauwasserverdunstung
- Sehr leise, lediglich 43 dB(A) für ein angenehmes Arbeiten
- Selbstschließende Tür
- Kabeldurchführung
- Potentialfreier Kontakt



Lila-LAB GmbH
Am Eichenhain 2 – D-31552 Rodenberg
Tel. 05723 / 74 96 14
info@lila-lab.de

Technisches Datenblatt
Haier Biomedical Pharmazeutischer
Kühlschrank
Model: HYC-290

Model		HYC-290	
Technical Data	Cabinet Type	Upright, Single Door	
	Climate Class	ST	
	Cooling Type	Forced Air Cooling	
	Defrost Mode	Auto	
	Refrigerant	R600a	
	GWP (global warming potential)	20	
	Sound Level (dB(A))	43	
Performance	Temperature Range (°C)	2-8	
Control	Will the fan stop automatically when opening the door	Y	
	Controller	Microprocessor	
	Display	LED	
Electrical Data	Power Supply (V/Hz)	220-240/50/60	115/60
	Electrical Current (A)	1.8	2.2
Performance Characteristics	Temperature Sensor	Digital Sensor	
	Power Consumption (kWh/24h)	4.4	5.1
Dimensions	Capacity (L/Cu.Ft)	290/10.2	
	Net/Gross Weight (approx)	(kg)	105/127
		(lbs)	231.6/280.1
	Interior Dimension (W*D*H)	(mm)	530*555*1080
		(in)	20.9*21.9*42.5
	Exterior Dimension (W*D*H)	(mm)	665*710*1665
		(in)	26.2*28.0*65.6
	Packing Dimension (W*D*H)	(mm)	700*810*1810
		(in)	27.6*31.9*71.3
Alarms	Container Load (20°/40°/40°H)	22/44/44	
	High/Low Temperature	Y	
	Remote Alarm	Y	
	Power Failure	Y	
	Sensor Error	Y	
	Low Battery	Y	
	Door Ajar	Y	
	Audible and Visual Alarm	Y	
Accessories	Caster	Y	
	Foot	Y	
	Porthole	Y	
	Shelves/Drawers	5/-	
	USB Interface	Optional	Y
	Printer	Optional	
Material	Exterior Material	Painted Steel	
	Interior Material	Polystyrene	
	Door Thickness (mm)	40	
	Cabinet Thickness (mm)	40	
	Shelves Material	Steel Wire, Coated with Plastic	
	No. of Shelves	5	
Other	Certificate	CE	UL