





Haier HYC-309

+5°C Pharmazeutischer Kühlschrank Inklusive Glastür 309 Liter mit Geregelter Umluftkühlung

- Mikroprozessor gesteuertes Digitaldisplay
- Glastür
- LED-Innenlicht
- Umweltfreundliches Kältemittel (R600a) mit einem sehr geringen Energieverbrauch
- Anzeige der Temperatur und der Gerätezustände
- Abschließbar
- Optische und Akustische Alarme für Temperaturabweichungen und andere Gerätezustände
- Sehr homogene Temperaturverteilung durch geregeltes Umluftkühlsystem (±2°C)
- Automatisches Abschalten bei öffnen der Fronttür
- Automatische Abtaufunktion mit Tauwasserverdunstung
- Sehr leise, lediglich 41 dB(A) für ein angenehmes Arbeiten
- Selbstschließende Tür
- Kabeldurchführung
- Potentialfreier Kontakt





Lila-LAB GmbH Am Eichenhain 2 – D-31552 Rodenberg Tel. 05723 / 74 96 14 info@lila-lab.de Technisches Datenblatt Haier Biomedical Pharmazeutischer Kühlschrank Model: HYC-309

	Model		HYC-309
	Cabinet Type		Upright, Ŝingle Door
Technical Data	Člimate Člass		N
	Cooling Type		Forced Air Cooling
	Defrost Mode		Auto
	Refrigerant		R600a
	GWP (global warming potential)		20
	Sound Level (dB(A))		41
Performance	Temperature Range (°C)		2-8
Control	Will the fan stop automatically when opening the door		Υ
	Controller		Microprocessor
	Display		LED
Electrical	Power Supply (V/Hz)		220-240/50/60
Data	Electrical Current (A)		1.9
Performance	Temperature Sensor		NTĊ
Characteristics	Power Consumption (kWh/24h)		4.5
	Capacity (L/Cu.Ft)		309/10.9
Dimensions	Net/Gross Weight (approx)	(kg)	77/87
		(lbs)	170/192
	Interior Dimension (W*D*H)	(mm)	525*500*1290
		(in)	20.7*19.7*50.8
		(mm)	600*630*1840
	Exterior Dimension (W*D*H)	(in)	23.6*24.8*72.4
		(mm)	680*690*1940
	Packing Dimension (W*D*H)	(in)	26.8*27.1*74.4
	Ct-:1 (20/(40/(40/1))	(ii iy	24/51/51
Alarms	Container Load (20'/40'/40'H)		Y Y
	High/Low Temperature		Y
	Remote Alarm		Y
	Power Failure		' Y
	Sensor Error		Y
	Low Battery		Y
	Door Ajar		
	Audible and Visual Alarm		Y
Accessories	Caster		Y
	Foot		
	Porthole		Υ
	Shelves/Drawers		5/-
	USB Interface		Optional
	Printer		Optional
Material	Exterior Material		Painted Steel
	Interior Material		Polystyrene
	Door Thickness (mm)		40
	Cabinet Thickness (mm)		38
	Shelves Material		Steel Wire, Coated with Plastic
	No. of Shelves		5
Other	Certificate		ĆE, UKĆA