



Haier DW-30L528D

-30°C Pharmazeutischer Gefrierschrank 531 Liter als Doppeltür-Version



- Mikroprozessor gesteuertes Digitaldisplay
- Massivtür
- Umweltfreundliches Kältemittel mit einem sehr geringen Energieverbrauch
- Anzeige der Temperatur und der Gerätezustände
- Abschließbar
- Optische und Akustische Alarme für Temperaturabweichungen und andere Gerätezustände
- Sehr homogene Temperaturverteilung durch Direkt-Kühlsystem
- Sehr leise, lediglich 39 dB(A) für ein angenehmes Arbeiten Selbstschließende
- Tür Kabeldurchführung
- Potentialfreier Kontakt





Lila-LAB GmbH Am Eichenhain 2 – D-31552 Rodenberg Tel. 05723 / 74 96 14 info@lila-lab.de



Technisches Datenblatt Haier Biomedical Pharmazeutischer Gefrierschrank -30°C Model: DW-30L528D

Model			DW-30L528D			
	Cabinet Type		U	Upright (Double Door)		
Technical Data	Climate Class	SNN				
	Cooling Type	Direct Cooling				
	Defrost Mode	Manual				
	Refrigerant	HC				
	Sound Level (dB(A))		39 43		43	
Performance	Cooling Performance (°C)			-30		
	Temperature Range (°C)		-1030			
Control	Controller		Microprocessor			
	Display		LCD			
	Power Supply (V/Hz)		220-240/50		115/60	
Electrical Data	Power (W)		460		420	
	Capacity (L/Cu.Ft)		531/18.8			
Dimensions	Net/Gross Weight (approx)	kg	180/205			
		lbs	396.8/451.9			
	Interior Dimension (W×D×H)	mm	704*620*1230			
		in	27.7*24.4*48.4			
	Exterior Dimension (W×D×H)	mm	940*845*1878			
		in	37.0*33.3*73.9			
		mm	1005*940*2040			
	Packing Dimension (W×D×H)	in	39.6*37.0*80.3			
	Container Load (20'/40'/40'H)			10/22/24		
Alarms	High/Low Temperature		Y			
	Remote Alarm		Υ			
	Power Failure		Y			
	Sensor Error		Υ			
	Low Battery		N			
	High Ambient Temperature		Υ			
	Dirty Condenser		N			
	Door Ajar		Y			
Accessories	Casters		Y(4)			
	Leveling Feet		Y(2)			
	Porthole		Y, 1*Left Side	Y, 1*Left Side, 1*Right Side, (25mm)Diameter		
	Inner Doors			N		
	Drawers		10- P	10- Plastic Drawers, Optional		
	Shelves		3- A	3- Adjustable Wire Shelves		
	Shelf Dimensions (W×D)(mm)			680*537		
	Max. Load per Shelf (kg)			37		
	USB Interface			Optional		
	RS485			Optional		
	NFC			N		
	Temperature Recorder			Optional		
Others	Certificate		CE, MDR		UL	